



Es

■ Mayor resistencia al desgaste y mejor durabilidad del neumático, incluyendo una banda de protección en su pared lateral.



■ La fina estructura del carbón super abrasivo aumenta el punto de unión entre el polímero y el carbón, mejorando el refuerzo del caucho y, a su vez, la resistencia al desgaste y la estabilidad de conducción.

■ Distribución optimizada de las costillas, con costillas centrales alargadas, que mantiene presión constante en toda la superficie de contacto.

■ Perfil ancho y plano de la banda de rodado, que mantiene un área de contacto máximo en cualquier superficie y en cualquier condición.

■ Perfil circular con mejora de la flexibilidad en la pared lateral, permitiendo una retroalimentación armoniosa y consistente, particularmente en curvas y durante los cambios de carril.

En

■ *Greater resistance to wear and better durability of the tire, including a protection band on its sidewall.*

■ *The fine structure of super abrasive carbon increases the bond between the polymer and carbon, improving rubber reinforcement and, in turn, wear resistance and driving stability.*

■ *Optimized rib distribution, with elongated central ribs, which maintains constant pressure across the entire contact surface.*

■ *Wide and flat tread profile, which maintains maximum contact area on any surface and under any condition.*

■ *Circular profile with improved flexibility in the sidewall, allowing for harmonious and consistent feedback, particularly in curves and during lane changes.*

SIZE TAMAÑO	LOAD INDEX/ SÍMBOLO DE VELOCIDAD ÍNDICE DE CARGA/ SÍMBOLO DE VELOCIDAD	PR	TT/TL	OVERALL DIAM (mm) DIÁMETRO TOTAL (mm)	SECTION WIDTH (mm) ANCHO DE SECCIÓN (mm)	MEASURING RECOMENDADO (pulgadas) TAMAÑO DE ARO RECOMENDADO (pulgadas)	RIM WIDTH APPROVED (inch) APROBADO (pulgadas)		DEPTH (mm) PROFUNDIDAD (mm)
							APPROVED (inch) APROBADO (pulgadas)	DEPTH (mm) PROFUNDIDAD (mm)	
145R12C	81/79P	8	TL	543	146	4.00	3.50 - 4.50		7.5
155R12C	88/86P	8	TL	578	155	4.50	4.00 - 5.00		8.2
165R13C	94/92R		TL	595	169	4.50	4.00 - 5.00		8.2
185R14C	102/100R		TL	650	186	5.50	5.00 - 6.00		8.2
195R14C	106/104R		TL	666	196	5.50	5.00 - 6.00		8.2
195R15C	106/104R		TL	690	196	5.50	5.00 - 6.00		8.2
195/70R15C	106/104S		TL	655	199	6.00	5.00 - 6.00		8.2
205/70R15C	112/110S		TL	669	207	6.00	5.50 - 6.50		8.2
215/65R16C	109/107T		TL	685	219	6.50	6.00 - 7.00		8.6
215/70R16C	108/106T	6	TL	708	218	6.50	5.50 - 7.00		8.6
195/75R16C	110/108N	10	TL	699	196	5.50	5.00 - 6.00		8.6